



Couplings & Connectors

Quality craftsmanship at an affordable price

4-Way Unions



Convert your 4-way union to fit any hose configuration

Designed to function as a stand-alone product or in conjunction with our line of specialty connectors, you can configure a 4-way union to meet any configuration

Description	Part #	Heat Treated	PSI Rating
3/8 Port 4-Way Union	402500	No	55,000 PSI
9/16 Port 4-Way Union	402501	No	55,000 PSI
3/8 Collar	402003	No	55,000 PSI
3/8 Gland Nut	402004	No	55,000 PSI
9/16 Collar	402005	No	55,000 PSI
9/16 Gland Nut	402006	No	55,000 PSI
3/8 Plug	402510	No	55,000 PSI
9/16 Plug	402511	No	55,000 PSI

Combine with any of our specialty connectors to create a Type-M style union for use in any situation.



Y-Block Connectors

Onsequeniet ides sum ex eaquis
consequa volorep elignate.



Split your UHP Water the right way - with a Y-Block designed to reduce flow restriction and turbulence.

Description	Part #	Heat Treated	PSI Rating
3/8 x 3/8 x 3/8 Port Y-Block	402550	No	55,000 PSI
9/16 x 3/8 x 3/8 Y-Block	402552	No	55,000 PSI
9/16 x 9/16 x 9/16 Y-Block	402554	No	55,000 PSI
3/8 Collar	402003	No	55,000 PSI
3/8 Gland Nut	402004	No	55,000 PSI
9/16 Collar	402005	No	55,000 PSI
9/16 Gland Nut	402006	No	55,000 PSI
3/8 Plug	402510	No	55,000 PSI
9/16 Plug	402511	No	55,000 PSI



L-Block Connectors

Choose Bingham Industries L-Blocks for routing rigid lance around corners and in to tight spaces.



Description	Part #	Heat Treated	PSI Rating
9/16 x 9/16 L-Block	402520	No	55,000 PSI
9/16 x 3/8 L-Block	402522	No	55,000 PSI
3/8 x 3/8 L-Block	402524	No	55,000 PSI
3/8 Collar	402003	No	55,000 PSI
3/8 Gland Nut	402004	No	55,000 PSI
9/16 Collar	402005	No	55,000 PSI
9/16 Gland Nut	402006	No	55,000 PSI
3/8 Plug	402510	No	55,000 PSI
9/16 Plug	402511	No	55,000 PSI



T-Block Connectors

The highest quality materials and machining practices are used with every piece we make



Give yourself options in the field with our T-Block Connectors. When used in conjunction with Type-M style adapters, the connection options are endless.

Description	Part #	Heat Treated	PSI Rating
9/16 x (2) 9/16 T-Block	402570	No	55,000 PSI
9/16 x (2) 3/8 T-Block	402572	No	55,000 PSI
3/8 x (2) 3/8 T-Block	402574	No	55,000 PSI
3/8 Collar	402003	No	55,000 PSI
3/8 Gland Nut	402004	No	55,000 PSI
9/16 Collar	402005	No	55,000 PSI
9/16 Gland Nut	402006	No	55,000 PSI
3/8 Plug	402510	No	55,000 PSI
9/16 Plug	402511	No	55,000 PSI

